

**OVERVIEW**



1. Headphone / microphone combo jack (3.5mm)	6. USB-C (USB 10Gbps), with DP 1.4
2. USB-A (USB 5Gbps)	7. USB-A (USB 5Gbps), Always On
3. USB-A (USB 5Gbps)	8. HDMI
4. Ethernet (RJ-45)	9. Power connector
5. USB-C (USB 10Gbps), with USB PD 65-100W & DP 2.1	

## PERFORMANCE

### Processor

#### Processor Family

13th Generation Intel® Core™ i7 or 14th Generation Intel® Core™ i7 / i9 Processor

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core i7-13650HX	14 (6 P-core + 8 E-core)	20	P-core 2.6GHz / E-core 1.9GHz	P-core 4.9GHz / E-core 3.6GHz	24MB	Intel® UHD Graphics
Core i7-14700HX	20 (8 P-core + 12 E-core)	28	P-core 2.1GHz / E-core 1.5GHz	P-core 5.5GHz / E-core 3.9GHz	33MB	Intel® UHD Graphics
Core i9-14900HX	24 (8 P-core + 16 E-core)	32	P-core 2.2GHz / E-core 1.6GHz	P-core 5.8GHz / E-core 4.1GHz	36MB	Intel® UHD Graphics

### AI (Artificial Intelligence)

#### AI PC Category

AI-Powered Gaming PC<sup>[1]</sup>

Notes:

[1] AI-Powered Gaming PCs feature Lenovo® AI Engine+ and NVIDIA® GeForce RTX™ GPUs to handle AI-driven tasks and deliver exceptional gaming performance.

### Operating System

#### Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

### Graphics

#### Graphics\*\*

Graphics	Type	Memory	Boost Clock	TGP	AI TOPS (Peak)	Key Features
NVIDIA® GeForce RTX™ 5050 Laptop GPU	Discrete	8GB GDDR7	2662 MHz	115W	440 TOPS	DLSS 4, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 5060 Laptop GPU	Discrete	8GB GDDR7	2497 MHz	115W	572 TOPS	DLSS 4, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 5070 Laptop GPU	Discrete	8GB GDDR7	2347 MHz	115W	798 TOPS	DLSS 4, DirectX® 12 Ultimate

### Monitor Support

#### Monitor Support<sup>[1]</sup>

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 8K@60Hz
- USB-C® supports up to 5K@60Hz

Notes:

[1] For Max resolution, DSC-enabled display is required.

### Chipset

#### Chipset

Intel® HM770 chipset

### Memory

### Max Memory<sup>[1]</sup>

- Up to 32GB DDR5-4800 offering
- Up to 32GB DDR5-5600 offering

### Memory Slots

Two DDR5 SO-DIMM slots, dual-channel capable

### Memory Type\*\*

- DDR5-4800
- DDR5-5600

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

## Storage

### Max Storage Support<sup>[1]</sup>

Up to two drives, 2x M.2 SSD

- M.2 2242 SSD up to 1TB each

### Storage Slot<sup>[2]</sup>

Two M.2 2280 PCIe® 4.0 x4 slots

### Storage Type

Disk Type	Interface	Offering
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

[2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.

PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);

PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);

PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

## Removable Storage

### Optical

None

### Card Reader

No card reader

## Multi-Media

### Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

### Speakers

Stereo speakers, 2W x2, audio by HARMAN, optimized with Nahimic Audio

### Microphone

Dual-microphone array

### Camera\*\*

- HD 720p, with E-shutter, fixed focus
- 5.0MP, with E-shutter, fixed focus

## Battery

### Battery\*\*

- 60Wh Rechargeable Li-ion Battery, supports Super Rapid Charge (10min charge 0-30% capacity, 30min charge 0-70% capacity, 80min charge 0-100% capacity)
- 80Wh Rechargeable Li-ion Battery, supports Super Rapid Charge (10min charge 0-30% capacity, 30min charge 0-70% capacity, 80min charge 0-100% capacity)

### Max Battery Life<sup>[1]</sup>

- Models with 60Wh battery:  
MobileMark® 30@250nits: 3.1 hr  
Local video (1080p) playback@150nits: 6.1 hr
- Models with 80Wh battery:  
MobileMark® 30@250nits: 4.2 hr  
Local video (1080p) playback@150nits: 9 hr

Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

## Power Adapter

### Power Adapter\*\*[1]

- 170W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 245W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

## Special Features

### Special Features

AI Chip: LA1

## DESIGN

## Display

### Display\*\*

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
15.1"	WQXGA (2560x1600)	Non-touch	OLED	1000nits (HDR peak) / 500nits (SDR typical)	Glossy	16:10	1,000,000:1	100% DCI-P3	165Hz	89° / 89° / 89° / 89°	DisplayHDR™ True Black 600, Dolby Vision®, TÜV Low Blue Light, TÜV Rheinland® Flicker Free
15.3"	WUXGA (1920x1200)	Non-touch	IPS[1]	300nits	Anti-glare	16:10	1000:1	100% sRGB	165Hz VRR	89° / 89° / 89° / 89°	Dolby Vision®, TÜV Low Blue Light

### Touchscreen

Non-touch

### Screen-to-Body Ratio

- IPS models: 90.9% AAR (active area ratio)
- OLED models: 90% AAR (active area ratio)

### Color Calibration

X-Rite® factory color calibration

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

## Input Device

### Pen

No support

### Keyboard

6-row, multimedia Fn keys, numeric keypad, key travel 1.6mm, cap recess 0.3mm, Copilot key

### Keyboard Backlight\*\*

- 24-Zone RGB backlight
- White backlight

### Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

## Mechanical

### Dimensions (WxDxH)<sup>[1]</sup>

Models	Dimensions
Models with IPS panel	344.9 x 255.35 x 22.50-23.99 mm (13.58 x 10.05 x 0.89-0.94 inches)
Models with OLED panel	344.9 x 255.35 x 19.95-21.54 mm (13.58 x 10.05 x 0.79-0.85 inches)

### Weight<sup>[2]</sup>

Models	Weight
Models with IPS panel	Starting at 2.1 kg (4.63 lbs)
Models with OLED panel	Starting at 1.9 kg (4.19 lbs)

### Case Color

Eclipse black

### Case Material\*\*

- Models with IPS panel: PC-ABS + 15% Talc (top), PC-ABS + 15% Talc (bottom)
- Models with OLED panel: Aluminium (top), PC-ABS + 15% Talc (bottom)

### Surface Treatment\*\*

- Models with IPS panel: Painting
- Models with OLED panel: Aluminium stamping (anodized with sandblasting)

### System Lighting

No system lighting

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

## CONNECTIVITY

### Network

#### WLAN + Bluetooth®\*\*<sup>[1]</sup>

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card<sup>[2]</sup>
- Wi-Fi® 7, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, M.2 card<sup>[3]</sup>

#### WWAN

No support

#### Ethernet<sup>[4]</sup>

Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

Notes:

[1] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Wi-Fi® 6 operation is subject to the regulation rules in each country.

[3] Wi-Fi® 7 operation is subject to the regulation rules in each country.

[4] Wake-on-LAN needs the AC adapter plugged in and the system in S3 mode (sleep mode). Since Wake-on-LAN is enabled by default, there are no options displayed in the BIOS.

## Ports<sup>[1]</sup>

### Standard Ports

- 2x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with USB PD 65-100W and DisplayPort™ 2.1<sup>[2]</sup>
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with DisplayPort™ 1.4
- 1x HDMI® 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Power connector

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

[2] Supports Lenovo® protocol for 140W charging but requires a unique Lenovo® adapter for operation.

## Docking

### Docking

Various docking solutions supported via USB-C®.

For more compatible docking solutions, please visit [Docking for Legion 5 15IRX10](#)

## SECURITY & PRIVACY

## Security

### Security Chip

Firmware TPM 2.0 integrated in chipset

### Fingerprint Reader

No fingerprint reader

### BIOS Security

- Master hard disk password
- Power-on password
- Supervisor password
- User hard disk password
- User password
- Self-healing BIOS
- More BIOS security features, please visit [BIOS Simulator<sup>\[1\]</sup>](#)

### Other Security

E-shutter

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

## SERVICE

## Warranty

### Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

## ACCESSORIES

## Bundled Accessories

### Bundled Accessories<sup>\*\*\*[1]</sup>

- Lenovo® Legion™ Gaming Speed Mouse Pad M
- Lenovo® Legion™ M300s RGB Gaming Mouse (USB connector)
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for Legion 5 15IRX10](#).

## OPERATING REQUIREMENTS

### Operating Environment

#### Temperature<sup>[1]</sup>

At altitudes up to 2438 m (8,000 ft)  
- Operating: 5°C to 35°C (41°F to 95°F)  
- Storage: 5°C to 43°C (41°F to 109°F)

#### Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications

- ErP Lot 6/26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

### Other Certifications

#### Other Certifications

- (Optional) TÜV Rheinland® Flicker Free
- TÜV Rheinland® Low Blue Light (Hardware Solution)

- Feature with \*\* means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with \*\*\* means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. **LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

