

## OVERVIEW



1. NOVO button hole	5. Power connector *
2. Card reader	6. USB-C 3.2 Gen 1
3. USB 3.2 Gen 1	7. HDMI
4. USB 3.2 Gen 1 (Always On)	8. Headphone / microphone combo jack (3.5mm)

### Notes:

- Ports with \* are only available on selected models

## PERFORMANCE

### Processor

#### Processor Family

10th Generation Intel® Core™ i3 / i5 / i7 Processor

### Operating System

#### Operating System\*\*

- Windows® 10 Pro 64
- Windows 10 Home 64
- Windows 10 Home in S mode
- FreeDOS
- No operating system

### Monitor Support

#### Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI supports up to 3840x2160@30Hz
- USB-C supports up to 3840x2160@60Hz

### Chipset

#### Chipset

Intel SoC (System on Chip) platform

### Memory

#### Max Memory<sup>[1]</sup>

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable
- 12GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

#### Memory Slots\*\*

- Memory soldered to systemboard, no slots, single-channel (4GB model)
- Memory soldered to systemboard, no slots, dual-channel (8GB, 12GB, or 16GB model)

#### Memory Type

DDR4-3200

#### Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

### Storage

#### Storage Support<sup>[1]</sup>

- Model with 45Wh or 57Wh battery: up to two drives, 1x 2.5" HDD + 1x M.2 SSD
  - 2.5" HDD up to 1TB
  - M.2 2242 SSD up to 512GB
  - M.2 2280 SSD up to 1TB
  - Optional Intel Optane™ Memory integrated with SSD, M.2
- Model with 70Wh battery: one drive, 1x M.2 SSD
  - M.2 2242 SSD up to 512GB
  - M.2 2280 SSD up to 1TB
  - Optional Intel Optane Memory integrated with SSD, M.2

#### Storage Slot

- Model with 45Wh or 57Wh battery: one 2.5" drive slot + one M.2 slot
  - One 2.5" drive slot, supports 2.5" SATA HDD
  - One M.2 2280 PCIe® Gen 3x4 slot, supports M.2 2242/2280 SSD
- Model with 70Wh battery: one M.2 slot
  - One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD

#### Storage Type\*\*\*

Disk Type	Interface	RPM
2.5" SATA HDD	SATA 6Gb/s	5.4K
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x2	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-
Intel Optane Memory with Solid State Storage, M.2 2280	PCIe NVMe, PCIe 3.0 x4	-

**Notes:**

- The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

## Removable Storage

**Optical**

- USB external DVD burner (DVD±RW), 9.5mm high
- None

**Card Reader**

4-in-1 card reader (SD, SDHC, SDXC, MMC)

## Multi-Media

**Audio Chip**

High Definition (HD) Audio

**Speakers**

Stereo speakers, 2W x2, optimized with Dolby® Audio™

**Microphone**

Dual array microphone

**Camera**

HD 720p webcam, with privacy shutter, fixed focus

## Battery

**Battery\*\***

- Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W or 95W AC adapter
- Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W or 95W AC adapter
- Integrated Li-Polymer 70Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 95W AC adapter

**Max Battery Life<sup>[1]</sup>**

- MobileMark® 2014: 11 hr (57Wh)
- MobileMark 2014: 15 hr (70Wh)
- MobileMark 2014: 9 hr (45Wh)

**Notes:**

- All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

## Power Adapter

**Power Adapter\*\*<sup>[1]</sup>**

- 45W round tip (2-pin, wall-mount) AC adapter, 100-240V, 50-60Hz
- 65W round tip (2-pin, wall-mount) AC adapter, 100-240V, 50-60Hz
- 65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 95W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

**Notes:**

- AC adapter offerings depend on the country.

## DESIGN

## Display

### Display\*\*<sup>[1]</sup>

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
15.6"	FHD (1920x1080)	None	TN	250 nits	Anti-glare	16:9	-	45% NTSC	-	-
15.6"	FHD (1920x1080)	None	IPS	300 nits	Anti-glare	16:9	-	45% NTSC	-	-
15.6"	FHD (1920x1080)	None	IPS	300 nits	Anti-glare	16:9	-	100% sRGB	-	-
15.6"	FHD (1920x1080)	Multi-touch	IPS	300 nits	Anti-glare	16:9	-	45% NTSC	-	-

### Touchscreen

- On-cell capacitive-type multi-touch, supports 10-point touch
- Non-touch

### Notes:

1. California Electronic Waste Recycling Fee  
 In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.  
 For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

## Input Device

### Keyboard

6-row, multimedia Fn keys, numeric keypad

### Keyboard Backlight

- LED backlight
- Non-backlight

### Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 69 x 104 mm (2.72 x 4.09 inches)

## Mechanical<sup>[1]</sup>

### Dimensions (WxDxH)

Models	Dimensions
Aluminium (top), PC + ABS (bottom) model	356.67 x 233.13 x 17.9 mm (14.04 x 9.18 x 0.70 inches)

### Weight

Around 1.66 kg (3.66 lbs)

### Case Color\*\*

- Abyss blue
- Graphite grey
- Light teal
- Platinum grey

### Surface Treatment

Anodizing

### Case Material

Aluminium (top), PC + ABS (bottom)

### Notes:

1. The system dimensions and weight vary depending on configurations.

## CONNECTIVITY

### Network

**Onboard Ethernet**

No Ethernet

**WLAN + Bluetooth®\*\*<sup>[1]</sup>**

- Wi-Fi® 5, 802.11ac 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card

**Notes:**

1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation

**Ports<sup>[1]</sup>****Standard Ports**

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery 3.0, and DisplayPort™ 1.2)
- 1x HDMI 1.4b
- 1x Card reader
- 1x Headphone / microphone combo jack (3.5mm)

**Optional Ports**

1x Power connector (model with plastic bottom)

**Notes:**

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.  
USB 2.0: 480 Mbit/s;  
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;  
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;  
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;  
Thunderbolt™ 3/4: 40 Gbit/s

**SECURITY & PRIVACY****Security****Security Chip**

Firmware TPM 2.0 integrated in SoC

**Fingerprint Reader**

- Touch style fingerprint reader on power button
- No fingerprint reader

**BIOS Security**

- Administrator password
- User password
- Master hard disk password
- User hard disk password

**Other Security**

Camera privacy shutter

**SERVICE****Warranty****Base Warranty\*\*<sup>[1]</sup>**

- 1-year depot service
- 1-year depot with 2-year system board service (Korea only)
- 2-year (1-yr battery) depot service

**Notes:**

1. More information of warranty policy, please access <https://pcsupport.lenovo.com/warranty>

**ENVIRONMENTAL**

## Operating Environment

### Temperature<sup>[1]</sup>

- At altitudes up to 2438 m (8,000 ft)
  - Operating: 5°C to 35°C (41°F to 95°F)
  - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

### Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

### Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

## CERTIFICATIONS

### Green Certifications

#### Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

