

NEC MultiSync® EA244WMi LCD 24" Enterprise Display

Datasheet



NEC MultiSync® EA244WMi features an extremely thin LED backlight panel with IPS technology which results in an ultramodern and slim design in combination with a premium feature set for the corporate office use. Ambient Light and Human Sensors enforce the sustainable product concept while offering improved ergonomics with 130 mm height adjustability. Moreover the display offers broad connectivity with three inputs DisplayPort, DVID and D-Sub. Thanks to its excellent IPS image quality with wide viewing angles in 16:10 screen format, it offers a high level of ergonomic comfort.

Ideal for the corporate that demand style and future proof technology.

Benefits

Feature Set for Perfect Office Use - Integrated Speakers, headphone jack and USB Hub provide excellent options for office communication.

Green Product Concept - Eco Mode and Carbon Footprint Meter / Carbon Savings Meter, Ambient Light Sensor.

Ambient Light Sensor - with Auto Brightness function always sets optimised brightness level according to ambient light and content conditions.

Easy Control - of up to six displays in a multi-monitor configuration with ControlSync® technology.

Human Sensor - detects the presence of a person in front of the screen; display switches on/off automatically depending on the presence of the user.

Product Information

Product Name	NEC MultiSync® EA244WMi
Product Group	LCD 24" Enterprise Display
Order Code	60003414 (BK), 60003409 (WH)

Display

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	24 / 61
Screen Aspect Ratio	16:10
Pixel Pitch [mm]	0.270
Brightness (typ.) [cd/m ²]	350
Contrast Ratio (typ.)	1000:1 (25000:1 dynamic contrast ratio)
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6
Colours [Mio.]	16.77

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 77
Vertical Frequency [Hz]	56 - 60

Resolution

Optimum Resolution	1920 x 1200 at 60 Hz			
Supported	1024 x 768; 1280 x 1024; 1280 x 720; 1280 x 768;	1280 x 960; 1360 x 768; 1366 x 768; 1400 x 1050;	1440 x 900; 1600 x 1200; 1680 x 1050; 1920 x 1080;	1920 x 1200; 640 x 480; 800 x 600

Connectivity

Digital	1 x DisplayPort; 1 x DVI-D (with HDCP); 1 x HDMI; USB ver. 2.0 (4 down / 1 up)
Analog	1 x mini D-sub 15 pin

Electrical

Power Consumption on Mode [W]	16 (Eco Mode); 19 (typ.); 29 (max.)
Power Savings Mode [W]	0.47

Power Supply	internal power supply
--------------	-----------------------

Environmental Conditions

Operating Temperature [°C]	+5 to +35
----------------------------	-----------

Operating Humidity [%]	20 to 80
------------------------	----------

Ergonomics

Height adjustable Stand [mm]	130
------------------------------	-----

Screen Tilt / Swivel [°]	-5 to +30; -170 to +170
--------------------------	-------------------------

Screen Rotate [°]	0 to 90 (landscape to portrait mode)
-------------------	--------------------------------------

Mechanical

Dimensions (W x H x D) [mm]	556.2 x 408.9 x 230
-----------------------------	---------------------

Weight [kg]	7.5
-------------	-----

VESA Mounting [mm]	100 x 100
--------------------	-----------

Additional Features

Special Characteristics	Ambient light sensor for optimized brightness levels; Carbon Footprint Meter; Carbon Savings Meter; ControlSync®; Customize Setting; DICOM preset; DICOM simulation; EcoModes; ErgoDesign®: Height adjustable stand (130 mm) with 90° Pivot features; Human Sensor; LED Backlight Technology; NaViSet Administrator 2; sRGB Support; Touch Sensor Keys; USB ver. 2.0 (4 down / 1 up)
-------------------------	--

Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
-----------------	--

Cable Management	yes
------------------	-----

Kensington security slot	yes
--------------------------	-----

Plug and Play	VESA DDC2B; VESA DDCi
---------------	-----------------------

Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)
-------	---

Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRGB
------------------	--

Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Setup Guide; USB Cable
------------------	---

Safety and Ergonomics	CE; EnergyStar 6.0; FCC Class B; GEEA/Energy Label; ISO 9241-307 (pixel failure class I); MPR III; PCT/Gost; RoHS; TCO 6.0; TCO Edge Certified 1.2; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA
Warranty	3 years warranty incl. backlight; optional 4th to 5th year warranty extension

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 28 kWh (based on 4 operating hours per day); Energy efficiency class: A+; Human sensor; Intelligent power management
Ecological Materials	Downloadable manuals
Ecological Standards	Energy Star 6.0; TCO Edge

* EnergyStar 6.0



CE



TÜV GS



TÜV Ergonomics



TCO Edge Certified 1.2



TCO 6.0



RoHS



ME06

PCT/Gost



MPR III



GEEA/Energy Label



FCC Class B

This document is © 2024 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.10.2024