

Samsung ML-2580N laser printer 1200 x 1200 DPI A4

Brand : Samsung  
Product code: ML-2580N  
Product name : ML-2580N

ML-2850N Mono printer 24ppm, 1200x1200dpi, 12000 sheets, USB 2.0, Ethernet 10/100 Base-TX, Windows, Mac OS  
Samsung ML-2580N. Print technology: Laser. Number of print cartridges: 1, Maximum duty cycle: 12000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 24 ppm. Network ready



Printing		Ports & interfaces	
Colour *	✗	USB 2.0 ports quantity	1
Print technology *	Laser	Network	
Duplex printing *	✗	Network ready	✓
Maximum resolution *	1200 x 1200 DPI	Wi-Fi *	✗
Print speed (black, normal quality, A4/US Letter) *	24 ppm	Ethernet LAN *	✓
Time to first page (black, normal)	9 s	Performance	
Features		Internal memory *	64 MB
Maximum duty cycle *	12000 pages per month	Processor frequency	360 MHz
Number of print cartridges *	1	Sound pressure level (printing)	50 dB
Input & output capacity		Sound power level (standby)	26 dB
Total input capacity *	250 sheets	Design	
Total output capacity *	80 sheets	Display	✗
Paper handling		System requirements	
Maximum ISO A-series paper size *	A4	Mac operating systems supported	Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard
Maximum print size	210 x 297 mm	Weight & dimensions	
Paper tray media types *	Bond paper, Envelopes, Labels, Plain paper, Recycled paper, Transparencies	Weight	7.3 kg
Multi-purpose tray media types	Bond paper, Envelopes, Labels, Letterhead, Plain paper, Preprinted forms, Recycled paper, Transparencies	Dimensions (WxDxH)	360 x 389 x 197 mm
ISO A-series sizes (A0...A9) *	A4, A5, A6	Other features	
ISO B-series sizes (B0...B9)	B5	Mac compatibility	✓
Non-ISO print media sizes	Executive, Folio, Letter, Oficio, Legal	Networking features	Ethernet 10/100 Base-TX
JIS B-series sizes (B0...B9)	B5	Toner cartridge	MLT-D1052S, MLT-D1052L
Ports & interfaces		Compatible operating systems	Win 2000/XP/Vista/7/2003 Server/2008 Server, Mac OS X 10.3 - 10.6, Linux OS
Standard interfaces	USB 2.0	Emulations	PCL6, PCL5e, SPL
		Power LED	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-AUG-2024. Prints or copies of Information are only valid on the printed Publication date