

## Samsung SCX-4729FD multifunction printer Laser A4 1200 x 1200 DPI 28 ppm

**Brand :** Samsung

**Product code:** SCX-4729FD

**Product name :** SCX-4729FD

28ppm, 1200x1200dpi, Fax/Print/Copy/Scan, 128MB, USB 2.0/Fast Ethernet, 10.3kg, White  
 Samsung SCX-4729FD. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 1200 x 1200 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 1200 DPI. Faxing: Mono faxing. Maximum ISO A-series paper size: A4



Printing		Input & output capacity	
Print technology *	Laser	Auto document feeder (ADF) output capacity	40 sheets
Printing *	Mono printing	Maximum input capacity	251 sheets
Duplex printing *	✓	Maximum output capacity	151 sheets
Maximum resolution *	1200 x 1200 DPI	<b>Paper handling</b>	
Print speed (black, normal quality, A4/US Letter) *	28 ppm	Maximum ISO A-series paper size *	A4
Time to first page (black, normal)	8 s	Maximum print size	216 x 356 mm
Economical printing	✓	Bond paper, Card stock, Envelopes, Labels, Plain paper, Pre-printed, Recycled paper, Thin paper, Transparencies	
DVD/CD printing	✗	Paper tray media types *	
<b>Copying</b>		ISO A-series sizes (A0...A9) *	A4, A5, A6
Copying *	Mono copying	ISO B-series sizes (B0...B9)	B5
Maximum copy resolution *	1200 x 1200 DPI	Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio
Copy speed (black, normal quality, A4)	28 cpm	JIS B-series sizes (B0...B9)	B5
Copy speed (colour, normal, US Letter)	29 cpm	Envelopes sizes	10, C5, C6, DL
Time to first copy (black, normal)	15 s	<b>Ports &amp; interfaces</b>	
Maximum number of copies	99 copies	Standard interfaces	Ethernet, USB 2.0
Copier resize	25 - 400%	Direct printing *	✗
<b>Scanning</b>		USB port	✓
Scanning *	Colour scanning	USB 2.0 ports quantity	1
Optical scanning resolution *	1200 x 1200 DPI	<b>Network</b>	
Maximum scan resolution	4800 x 4800 DPI	Wi-Fi *	✗
Scan technology	CIS	Ethernet LAN *	✓
Scan to	File	<b>Performance</b>	
Scan drivers	TWAIN, WIA	Card reader integrated	✗
Film scanning	✗	Internal memory *	128 MB
<b>Fax</b>		Sound pressure level (printing)	50 dB
Faxing *	Mono faxing	Sound pressure level (copying)	50 dB
Fax resolution (black)	300 x 300 DPI	Sound power level (standby)	26 dB
Modem speed	33.6 Kbit/s	Mac compatibility	✓
Fax memory	600 pages	<b>Design</b>	
Fax memory	8 MB	Market positioning *	Home & office
Auto-redialing	✓	Built-in display *	✓
Speed dialling	✓	Display	LCD
Fax speed dialing (max numbers)	200	Touchscreen	✗
Fax forwarding	✓	Display number of lines	2 lines
Fax broadcasting	209 locations		
Fax delayed sending	✓		

Fax		System requirements	
Auto reduction	✓	Windows operating systems supported	✓
<b>Features</b>		Mac operating systems supported	✓
Maximum duty cycle *	12000 pages per month	Linux operating systems supported	✓
Digital sender	✗	Server operating systems supported	Windows Server 2003, Windows Server 2008
Number of print cartridges *	1	<b>Weight &amp; dimensions</b>	
Printing colours *	Black	Weight	10.3 kg
Page description languages	PCL 5e, PCL 6, SPL	<b>Packaging content</b>	
<b>Input &amp; output capacity</b>		Drivers included	✓
Total number of input trays *	1	<b>Other features</b>	
Total input capacity *	250 sheets	Dimensions (WxDxH)	406 x 338 x 384 mm
Total output capacity *	150 sheets	Network ready	✓
Multi-Purpose tray	✓	Finishing option	✗
Multi-Purpose tray input capacity	1 sheets	All-in-one functions	Copy, Fax, Print, Scan
Paper input type	Cassette	Colour all-in-one functions	Scan
Auto document feeder (ADF)	✓	Colour scanning	✓
Auto document feeder (ADF) input capacity	40 sheets	Connectivity technology	Wired
		Duplex (double-sided)	✓
		Fax compatibility	ITU-T G3
		Legal	✓
		Resizing	✓



8806071436418



8806071437736



8806071547046



0635753612523



635753612523



8806071754741



8806071546056

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.