

Eaton 3SM36

Catalog Number: 3SM36

Eaton 3S Mini UPS, 36 W, Input: French, Outputs: (4) Barrel, Output voltages: DC 9V-3A, 12V-3A, 15V-2.4, 19V-1.89A, Tower

General specifications



Фото репрезентативне

Product Name	Catalog Number
Eaton 3S Mini UPS	3SM36
EAN	Product Length/Depth
3553340705014	136 mm
Product Height	Product Width
30 mm	95 mm
Product Weight	Warranty
0.37 kg	2 year
Compliances	Certifications
CE Marked	CE
	IEC/EN 62040-2
	IEC 62477-1
	IEC 62040-5-3
Model Code	
Eaton 3S Mini 36W	

Special features

Attractive design and glossy finish make the 3S a perfect fit for the modern office environment

Compact unit fits on or under your desk

4 Barrel adaptators to connect your device

LED indicator providing information about output voltage or remaining battery capacity

2200 mAh Battery (2 cells)

Topology

Offline

Form factor

Tower

Construction type

Free standing model

Color

Black/White

VA rating

72 VA

Wattage

36W

Rack mounting kit

No

Package contents

UPS

Input cable

(4) Barrel adaptators

Quickstart guide

Surge protection

No

Auto shutdown function

No

Primary frequency - max

70 Hz

Primary frequency - min

46 Hz

Input connection

Other

Input cord length

1 m

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input frequency range

46-70 Hz

Receptacle

(4) Barrel adaptators

Number of output connections French standard (Type E)

0

Number of Outputs C13

0

Number of Outputs C19

0

Number of outputs hardwired

0

Num of Outputs PC (SCHUKO)

0

Output nominal voltage

9 V (12/15/19 V)

Feed type

1

Voltage type

AC/DC

Runtime graph

\$row.attributeValue.cdata

Battery management

Replaceable batteries

Battery replacement

User replaceable

Battery rating

2200 mAh

Battery type

Lithium-ion

Extended battery capability

No

Runtime at half load

30 min

Expansion slots

No

Ethernet interface

No

Includes network card

No

User interface

LEDs

Type of interface

None

Potential free switch contact

No

Altitude

2000 m

Noise level

<25 dB at 1 meter

Relative humidity

0-85% non-condensing

Operating temperature - max

35 °C

Operating temperature - min

0 °C

Input voltage - max

240 V

Input voltage - min

100 V

Output voltage - max

19 V

Output voltage - min

12 V

Secondary frequency - min

0 Hz

Battery quantity

2

Efficiency

78

Efficiency (eco-mode)

0

Input voltage range

100-240 V

Output power factor

0

Phase (input)

1

Phase (output)

0

Runtime at full load

11 min

Voltage distortion output (linear load) - max

0



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. Усі права захищені.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)